

HOTSHOT[®] HD-S






The choice of IR professionals

Think you can't afford 640x480 resolution?

Think again. Introducing HotShot HD-S – the thermography professional's choice in high performance infrared cameras. HotShot HD integrates state-of-the-art infrared imaging technology, a new dual laser hotspot highlighter and software functionality created to address the demands of heavy duty infrared camera users. Stunning 640x480 infrared image details combined with an integrated, high-quality megapixel visible camera and advanced image fusion greatly improves image interpretation and the quality of infrared inspection reports.

HotShot HD also features an integrated inspection data logger and route management system that can bring new levels of productivity to your IR inspection program. HotShot's

highly intuitive graphical user touchscreen interface puts nearly all commands within a single touch, eliminating complex pull-down menu controls.



The World's First
Affordable
640x480 Resolution
Infrared Camera



HotShot HD – Simply the best value on the market today!

640x480 Resolution

- World's best image quality
- 500:1 measurement spot size – Increased accuracy
- Increased user safety – Inspect high voltage electrical circuits outside the shock boundary
- Highest thermal sensitivity – see thermal problems earlier

Easy To Use

- Lightweight ergonomic design
- Touchscreen interface simplifies inspection data collection
- Highly intuitive interface reduces learning curve
- Automated report generation increases productivity up to 90%

Innovative Design

- Unique dual laser target marking system
- Advanced image fusion
- Integrated route management software option
- Rotating camera head increases comfort when inspecting equipment

Affordable Performance

- Application-specific packages offered
- Lowest ownership costs over 5 years
- 640x480 performance for 320x240 camera prices



HOTSHOT[®] HDS

The choice of IR professionals

ERGONOMIC DESIGN

View Objects at All Different Levels

Floor Level¹

Only HotShot keeps you comfortable whether you crouch to maintain a perpendicular view or stand upright and rotate the IR eyeball down to view objects at floor level.



Strike Zone¹

(belt level)

Every user has a different preference about holding tools. HotShot's infinite position IR eyeball enables you to hold the camera in the most comfortable position for you first and then rotate the camera to point at the object.




Overhead¹

When viewing overhead objects HotShot's articulating IR eyeball ensures that you maintain line of sight and optimal viewing angle and wrist position.



Viewing Angle²

While today's LCD displays feature improved viewing angle performance, LCD displays still work best when viewed perpendicular.



¹ Notice viewing angle and grip angle do not change over range of object viewing levels.

² Human Factors Specification Mil-Std 1472f

Standard Configuration

| | |
|---------------------------|------------------------|
| HotShot HD-S | PC Card Adapter |
| Lithium-Ion Batteries (2) | Hardside Carrying Case |
| Universal AC Power Supply | Battery Charger |
| USB Cable – Mini B Jack | Operator Manual |
| ViewIR Desktop Software | 512MB CF Memory Card |
| ReportIR | |

Ordering Information

| Item | Description |
|--------|-----------------------------|
| 914832 | HotShot HD-S |
| 914756 | RoutelR Software |
| 914674 | Fault Tree Manager Software |
| 914636 | Rechargeable Batteries |

Specifications

| Imaging Performance | |
|--|---|
| Resolution | 640x480 |
| Detector Type | VOx Microbolometer |
| Sensitivity | 50mK (0.05°C) |
| Field of View / Min. Focus | 25°x18° / 0.4m |
| Frame Rate | 30Hz |
| Focus | Manual |
| Visible Camera | 1280x1024 pixels, flash, torch |
| Image Presentation | |
| Image Modes | IR/PIP/Fusion |
| Display | 3.5" 640x480 LCD touchscreen |
| Color Palettes | 6 |
| Measurement | |
| Temperature Range | -20°C to 350°C |
| Accuracy | ±2°C or ±2% (whichever is greater) |
| Spot Size Ratio | 500:1 (standard lens) |
| Measurement Modes | Point (5), Line, Area (user defined) |
| Measurement Correction | emissivity, background/transmission/ambient |
| Image Storage and Camera Functionality | |
| Digital Media | 512MB CF card (~600 hi-res images) |
| Internal Image Capacity | 512MB (~600 hi-res images) |
| Recording Modes | Snapshot/sequence (optional) |
| Image Annotation | Touchscreen data logger GUI |
| In-Camera Routing | Included |
| Target Marker | Dual laser line target identifier |
| Classification | Class 2 |
| Power | |
| Battery Type | Rechargeable Lithium-Ion |
| Battery Run Time | 2.5 hours |
| Battery Charging | 10-16VDC input. Charging status LED |
| AC Power Supply | 100-270 VAC, 50/60 Hz |
| Environmental | |
| Operating Temp. Range | -5°C to 50°C |
| Storage Temperature Range | -40°C to 70°C |
| Humidity | 10% to 95%, IEC 360 |
| Water and Dust | IP-54 |
| Shock /Vibration | 25G, IEC 68-2-29 / 2G, IEG 68-2-6 |
| Physical | |
| Weight | 2.7 lbs. |
| Dimensions (WxHxD) | 7.5" x 7.5" x 3" |
| Interfaces | |
| Real-Time Digital Output | USB 2.0 (optional) |
| Image Transfer | USB 2.0, CF card |
| Video | NTSC |
| Desktop Software | |
| ViewIR™ | Included |
| ReportIR™ | Automatic multi-page report |
| RoutelR™ | Thermography program management software package (optional) |
| Fault Tree Manager™ | Equipment-type editor (optional) |



373 Route 46, Fairfield, NJ 07004 973-882-0211 Fax: 973-882-0997
www.electrophysics.com

Proudly designed and built in the USA.